
Energy Rating Index(ERI)

New opportunities for residential energy efficiency and code compliance in the 2015 IECC


Polly Ledvina, PhD PSL Integrated Solutions pledvina@pslintegrated.com



2015 IECC Compliance Paths

Prescriptive Path – 2009 & 2012 IECC
UA Trade Off Alternative – 2009 & 2012 IECC
Energy Cost Compliance – 2009 & 2012 IECC

Energy Rating Index (ERI) – new to 2015 IECC



What is the ERI?

The ERI score is defined as a numerical score where 100 is equivalent to the 2006 IECC and 0 is equivalent to a netzero home.

Each integer value on the scale represents a 1% change in the total energy use of the rated design relative to the total energy use of the ERI reference design.



ERI = RESNET's HERS Index


RESNET's HERS index, based on ANSI RESNET Standard 301-2014, is the existing compliant ERI method for inspecting and calculating a home's energy performance.



RESNET = Residential Energy Services Network, a not-for-profit, standards-making body for residential energy efficiency rating and certification systems in the United States

HERS = Home Energy Rating System

The RESNET HERS Index





ANNUAL ENERGY SAVINGS⁽²⁾ \$539 typical existing \$0 typical new home (\$/yr)* Your home is at the same level as a standard new home, which meets

the current industry standard for home energy efficiency. But that doesn't mean your home is working at its optimal efficiency! There are still many energy saving measures that you could implement to make your home much more energy efficient, resulting in a safer home environment, lower utility bills and a better effect on the environment.

http://www.resnet.us/hers-index-largescale

ERI Rating Variables

- All exterior walls (both above and below grade)
- Floors over unconditioned spaces (like garages or cellars)
- Ceilings and roofs
- Attics, foundations and crawlspaces
- Windows and doors, vents and ductwork
- HVAC systems, water heating system, and your thermostat
- Appliances and lighting
- House and duct air-tightness

The ERI performance path also requires builders to follow the mandatory code requirements of the IECC and comply with the minimum insulation and window envelope performance requirements of the 2009 IECC.

Table R406.4 Maximum ERI

Climate Zone	Energy Rating Index
1	52
2	52
3	51
4	54
5	55
6	54
7	53
8	53


Compliance based on an ERI requires the rated design to have an ERI less than or equal to the appropriate value listed in Table R406.3.

Except in Texas....

Climate Zone	Energy Rating Index	
1	52	
2	(52)	->
3	51	
4	54	
5	55	
6	54	
7	53	
8	53	

65 until 9/201963 until 9/202259 after that

(HB1736)





Looking for a HERS Rated Home?

Homes with HERS Index scores are more energy efficient, resulting in lower energy bills and higher home comfort. To find out if a home has been HERS-rated, enter its full address in fields below.

Enter Street Address		Enter City Name			
State *		Zip Code			
Select a State	~	Enter Zip Code	Q FIND		

https://www.resnet.us/public-access-to-resnetnational-registry#nr-form-title





"Above Code" Energy and Green-building Programs













KB Homes

Average HERS: 60

SUSTAINABILITY REPORT 2015



Beazer Homes


Average HERS:

65



David Weekly

Average HERS: 58



Chesmar Homes Average HERS:

63

Texas Veterans Home Loan and Home Improvement Programs

Certification of Eligibility Application



George P. Bush, Chairman

For assistance, please contact the Texas Veterans Land Board Toll free at 1-800-252-VETS (8387)

Last Update: April 27, 2016

Texas Veterans Land Board + George P. Bush, Chairman Stephen F. Austin Building + 1700 North Congress Avenue + Austin, Texas 7870-1-1496 P.O. Box 12873 + Austin, Texas 78711-2873 512.463.5660 + 000.252.VETS texasveterans.com To be eligible for a Texas Veterans Home Loan, all newconstruction homes must

meet the U.S. Environmental Protection Agency's ENERGY STAR® rating as an energy efficient home, or

have a HERS Index score of 75 or less.

Table 4.1. Baseline Characteristics Used in Assessing Volatility of Individual Building Characteristics

Building Characteristic	Baseline V alues Held Constant when Assessing V ol atility of Corresponding HERS Index V alues				
Gas'AC equipment efficiency	AFUE 78, SEER 13				
Heat pump equipment efficiency	HSPF 7.7, SEER 13				
Conditioned Floor Area (CFA)	2400 ft ²				
Window-Floor Ratio (WFR)	16%, except for HV AC efficiency runs, for which 15% was used				
ppliances	Standard appliances (no ENERGY STAR)				
oundation type	Crawlspace				
Number of stories (N_story)	Bream for the U.S. Department of Energy Preparation for the U.S. Department of Energy				
Drientation	Neutral (glazing equally distributed)				

Identification of RESNET HERS Index Values Corresponding to Minimal Compliance with the IECC Performance Path







Figure 4.2. Volatility of Corresponding HERS Index to Individual Characteristics: Zone 2, Moist

PNNL-22560 **ENERGY** Prepared for the U.S. Department of Brierg under Contrast DE ACM 76 PL01830 Identification of RESNET HERS Index Values Corresponding to Minimal Compliance with the IECC Performance Path Z Todd Taylor Vrushali Mendor May 2014 Pacific Northwest oudly Operated by Ballene Sinc

Conditioned Floor Area (CFA)

- At CFA = 2400 sf, HERS Index is about 76.
- At CFA = 5000 sf, HERS Index is about 70
- At CFA = 1200 sf, HERS Index is about 82



HVAC Equipment

- ► Gas/AC Efficiency
- Heat Pump Efficiency

Base = 78 AFUE, 13 SEER Base = 7.7 HSPF, 13 SEER

SystemType	Efficiency Level	Charge in Corre- sponding HERS Index
-	Base (AFUE 78, SEER 13)	0
Gas/AC Efficiency Level	High-efficiency l (AFUE 80, SEER 14)	-2
Gas/AC Eniciency Level	High-efficiency 2 (AFUE 80, SEER 16)	-5
	High-efficiency 3 (AFUE 80, SEER 20)	-8
Heat Pump Efficiency Level	Base (HSPF 7.7, SEER 13)	· 0
near rung Enidency Level	High-efficiency (HSPF 8.2, SEER 15)	-3

BARTHERE POINT OF POINT-22550 Point Concern DB AGE STRUCTURE
Identification of RESNET HERS Index Values Corresponding to Minimal Compliance with the IECC Performance Path
Z Todd Taylor Vfrushuli Mendon
May 2014
Pacific Northwest MICHAL LARGHOUSY Multiple LARGHOUSY Multiple Server 201

Equipment efficiency is directly accounted for in the HERS Index calculation but is ignored in the IECC Compliance Ratio.

High efficiency appliances

ENERGY STAR Appliances 3-4 points

Rating Audit		
Refrigerator Total Consumption: 727 k	Wh/yr	Location: Conditioned
Dishwasher Energy Factor: 0.46	or kWh/yr: 0	Place Setting Capacity: 12
Range/Oven Fuel: Natural gas 💌	Induction Range	Convection Oven
Clothes Washer and Dryer Location: Conditioned	Washe	er Presets: RESNET Default
Dryer Fuel: Natural gas Dryer Eff. Factor: 2.67	Washer MEF: 0.817 Washer LER: 704	Elec Rate: 0.0803 kWh/yr Gas Rate: 0.58
Moisture Sensing 🥅	Capacity 2.874 Cu.Ft:	Annual Gas Cost 23.00
	nterior Tixtures	Exterior Fixtures(%): 0.0 Garage Fixtures(%): 0.0
Ceiling Fan(s) CFM / Watt 0.0 (a	at Med. speed)	Restore RESNET Defaults


- More R-value than required by the 2009 IECC
- House orientation and window shading
- House tightness below 5 ACH50
- Reduced duct leakage to the outside
- Duct location (conditioned vs unconditioned space)
- Solar

2009 IECC vs. 2015 IECC Prescriptive Table

Climate Zone	Window U- Factor	Window SHGC	Ceiling R-Value	Wood Framed Wall R-Value	Mass Wall R-Value	Floor R-Value	Basement Wall R-Value	Slab R-Value and Depth	Crawi Space Wall R-Value
1	1.2 NR	0.30 0.25	R-30	R-13	R-3/4	R-13	0	0	0
2	0.65 <mark>0.40</mark>	0.30 0.25	R- 30 <mark>38</mark>	R-13	R-4/6	R-13	0	0	0
3	0.35 0.35	0.30 0.25	R-30 38	R-13 20 or 13+5	R-5/8 8/13	R-19	R-5/13	0	R-5/13
4 except Marine	0.35 0.35	NR 0.40	R-38 49	R-13 20 or 13+5	R-5/10 <mark>8/1</mark> 3	R-19	R-10/13	R-10, 2ft	R-10/13
S and Mairine 4	0.35 0.32	NR	R-38 49	R-20 or 13+5	R-13/17	R-30	R-10/13 15/19	R-10, 2ft	R-10/13 15/19
Climate Zone 6	0.35 <mark>0.32</mark>	NR	R-49	R-20 or 13+5 20+5 or 13+10	R-15/20	R-30	R-15/19	R-10, 4ft	R-10/13 15/19
Climate Zone 7 & 8	0.35 0.32	NR	R-49	R-21 20+5 or 13+10	R-19/21	R-38	R-15/19	R-10, 4ft	R-10/13 15/19

Orient house with highest percent of glazing on North and South sides

Use overhangs above south-facing windows ideally sized to shade glass in spring and fall, but not winter.



www.buildingtips.net

Reduce Infiltration below 5 ACH50





Reduce duct-leakagethere are no ductleakage limits using 2015 IECC performance pathways (unlike 2012 IECC)!

Locate ducts in conditioned space – and no duct-leakage testing will be required



HERS < 52 is not so easy without photovoltaics




2015 IECC ENERGY RATING INDEX REPORT Property Owner's Name Property Address Houston, TX 77005 Organization PSL Integrated 713-524-8352 HERS Based on Plans 2016-06-28 Rater ID:6448517 Annual Energy Consumption HERS Reference Rated Home Home (HSTU) nMUEL (HSTU) Rated Home Cost (\$/yr) Existing Homes Heating 41 23.4 1.5 30.5 248 Cooling 51.5 Water Heating 9.5 Blandard New Home Lights & Appliances Photowaltaico Total 116.7 61.5 1222 33 Annual Estimates Electric (kWh)c 9152 C02 Emissions(Tons): 264 Energy Savings (5)**: Natural gas(Therms): 11 *Based on standard operating conditions **Based on U.S. DOE designation of a HERS index of 130 as the Typical Existing Zero Energy Home TARGET INDEX: 5 HERS INDEX: 53 ctions 406.3 and 406.4 of the 2015 This home DOESN Kame Av 2014 Orga Mandatory Requirements HERS Target Duct Insulation (Ducts outside R-6, inside is R-0) 2009 IECC UA PAS Maximum Fenestration U-factor (2012) PASS Duct Testing (2015) Mechanical Ventilation PAST Modmum Fenergration SHGC (2012) PAS PAS Air Lenkage (5 ACH50 for CZ1-2, 3 ACH50 for CZ3-8) PAG Mechanical Ventilation Efficacy PASS PAS Mandatory Requirements Checkbox (2015 IECC) Emissions Data **Provider Data and Seal** ation Prev 4.7 Company 10.1 Address Carbon Dioxide (CO2) - tons/year Sulfur Dioxide (S02) - ibs/year 8.4 City, State, Zip Phone # trogen Öxides (NÖx) - Ibs/year Fax # REPURate - Residential Energy Analysis and Rating Software v15.1 This information does not corrotitute any warranty of energy cost or savings. © 1985-2016 Noresco, Boulder, Colorado.

5 kW PV Array HERS < 22



2015 IECC ENERGY RATING INDEX REPORT



RE//Rate - Residential Energy Analysis and Rating Software v15.1 This information does not constitute any warranty of energy cost or savings. © 1985-2016 Noresco, Boulder, Colorado.

Features to Improve Efficiency of Existing Homes

Mechanical equipment

- High efficiency furnace
- ► High efficiency AC
- High efficiency water heater
- More R-value than required by the 2009 IECC
- House orientation and window shading
- House tightness
- Reduced duct leakage to the outside
- Duct location (conditioned vs unconditioned space)
- CFL or LED Lighting
- High efficiency appliances
- Solar

Immediately Soonest Opportunity

Thank You!

Call or email: Polly Ledvina PSL Integrated Solutions <u>pledvina@pslintegrated.com</u> 713-825-7136